

ThinkCentre Tiny-In-One 24 Gen 4 [11GDPAT1EU](#)

Product

ThinkCentre T1024Gen4

Region

RUCIS

Machine Type

11GD

Color

Black

Display Size

23.8"

Touchscreen

None

Resolution

1920x1080

Aspect Ratio

16:9

Pixel Pitch

0.2745 mm

Dot / Pixel Per Inch

92.6 dpi

Brightness

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4-14 ms

Color Gamut

72%

View Angle (H / V)

178 / 178

Stand

Adjustable Stand

Camera

1080p

Power Consumption (Typical / Maximum)

15W / 27W

Power Supply

90W 88% Adapter

Base Warranty

3-year

Ann Date (mm/yy)

05/20



WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<https://psref.lenovo.com>

Visit psref website for the latest version of Product specifications Reference.

© Lenovo, 2020. All rights reserved.



Lenovo

ThinkCentre Tiny-In-One 24 Gen 4 Platform Specifications

Product Specifications Reference (PSREF)

Form factor	Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into the back of TIO, clean cabling and effortless setup			Mounting features	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPI® (100mm mount)		
Compatible Tiny:	P340 / P330 / P320 / M90q / M80q / M70q / M75q / M920(x) / M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny M90n / M75n Nano (with TIO kit)			Adjustable stand	Tilt: 30° back, -5° forward; lift: 5.9" (150mm); swivel: +/-45°; Pivot: clockwise -5° to 90°		
Panel	TFT-LCD, IPS (In Plane Switching) technology**, White LED backlight **Notes: IPS may refer to IPS, PLS, ADS, AHVA, AAS panels			Power supply	90 watts AC/DC adapter, 88% PSU, universal		
Viewable image size	23.8" (604.7mm) diagonal			Power consumption	27 watts max, 15 watts typical, <0.5 watts standby / suspend		
Max view area (W x H)	20.75" x 11.67" / 527.0mm x 296.5mm			Limited warranty	3-years, Carry-In or Courier service		
Bezel Width	Top / Side: 2mm, Bottom: 22.1mm			Environmental	TCO 8.0, TCO edge 2.0, ENERGY STAR® 8.0, EPEAT™ Silver rating, UL GREENGUARD Certified, Erp lot5, WEEE, RoHS, TUV Eye comfort		
Native resolution	1920x1080 @60Hz			Windows certifications	Windows 7 and Windows 10 certified		
Presets / user settings	25			Ship group	TIO (Monitor), detachable stand, power adapter, power cord, information flyer, user's guide, and driver CD		
Multi-touch	Optional 10-point multi-touch, AIT technology			Accessories	For compatible accessories, please go to http://smartfind.lenovo.com		
Aspect ratio	16:9						
Pixel pitch (mm)	0.2745mm						
Dot/Pixel per Inch	92.6 dpi						
Brightness	250 nits or cd/m² (typical)						
Contrast ratio	1000:1 (typical)						
Pixel response time	14ms (default), over drive to 4ms, 6ms						
Color gamut	72% NTSC (CIE 1931)						
Anti-reflective	Anti-glare						
Viewing angle at 10:1 CR	178° (+/- 89°) horizontal, 178° (+/- 89°) vertical						
On screen display	On screen display with digital user controls (8 languages)						
Control features	Font: Exit button, Up / Mode-switching button (TIO / monitor mode, switches the sources of both display and side USB port), Down / Brightness button, Enter / Menu button, Power button Bottom: Volume up button, Volume down button						
TIO Power On features	Pressing Alt + P (on keyboard) or Power button (on TIO) can turn on both TIO and Tiny (Some old Tiny cannot fully support, see compatible list)						
Side ports (on TIO)	One USB Type A port (The availability and version depends on the Tiny installed or the PC connected via USB upstream port)						
Side ports (on Tiny)	Side ports offered by installed Tiny (front ports)						
Rear ports	One DisplayPort in port, one USB upstream port, one power connector						
3-in-1 Cable	Undetachable 3-in-1 cable (Power connector, USB [supports USB 3.1 Gen1 / USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)						
Camera	Some: 1080p camera with dual microphone and Think Shutter Some: RGBIR camera with dual microphone, support Think Shutter						
Internal Speaker	2 watt x2						
Security	Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO together, more security features offered by Tiny installed (optional)						
Mechanical							
	Dimensions	TIO without stand	TIO with stand				
	W x D x H (inch)	21.25 x 2.57 x 14.47	21.25 x 9.07 x 17.59 - 23.5				
	W x D x H (mm)	539.8 x 65.3 x 367.6	539.8 x 230.4 x 446.9 - 596.9				
	Weight (Approx.)	7.96 lb /3.61 kg	12.92 lb /6.66 kg				

ThinkCentre Tiny-In-One 24 Gen 4 Compatible list			
Model	P340 / P330 / P320 M90q / M80q / M70q / M75q / M920(x) / M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny M90n / M75n (with TIO kit)	M93/p / M83 / M73 / M53 Tiny	Chromebox
Turn on TIO and Tiny together via Alt + P on USB KB	All models	All models	Not support
Turn on TIO and Tiny together via TIO Power Button	All models	Not support	All models

Lenovo, May 2020

Lenovo™

ThinkCentre Tiny-In-One 24 Gen 4

