

OVERVIEW



1. Power connector	3. USB-B 3.1 Gen 1
2. DisplayPort	4. USB 3.1 Gen 1

Notes:

• USB 3.1 Gen 1(only available when a Tiny is installed or a PC is connected)



PERFORMANCE

Panel

Panel

In-Plane Switching (IPS)

Backlight

WLED

Display Size

23.8 inches

Max View Area

WxH: 527 x 296.5 mm

Resolution

1920 x 1080

Aspect Ratio

16:9

Pixel Pitch

0.2745 x 0.2745 mm

Dot / Pixel Per Inch

92.6 dpi

Brightness

250 nits

Contrast Ratio

· Contrast Ratio: 1000:1

• Dynamic Contrast Ratio: 3M:1

View Angle (H / V)

Horizontal: 178°, Vertical: 178°

Response Time

Extreme Mode: 4 msNormal Mode: 6 ms

• Off Mode: 14 ms

Refresh Rate

60Hz

Color Gamut

72% NTSC

Color Support

16.7 Million

Color Depth

8-bit

Screen Surface Treatment

Anti-glare

Operating System

Operating System

- Windows® 7 Support
- Windows 10 Support

Multi-Media

Camera

- FHD 1080p, with dual microphone and Think Shutter
- IR + RGB camera, with dual microphone and ThinkShutter

Microphone

Dual-microphone array



Speakers

Stereo speakers, 2W x2

Power Supply

Power Consumption

Typical / Max: 15W / 27W

Voltage Required

AC 100 to 240 V (40-60Hz)

DESIGN

Display

Touchscreen

- (Optional) Advanced In-cell Touch (AIT), supports 10-point touch (for models 11GCPAT1 and 11GCPAR1 only)
- Non-touch

Mechanical

ThinkCentre® M Series Support

P340 / P330 / P350 / P350 / P360 / M90q / M80q / M70q / M75q / M920(x) / M720 / M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny / M90n / M75n Nano (with TIO kit)

Bezel Width

- · Bottom: 22.1mm
- Top / side: 2mm

Buttons

- Power button
- Volume button
- Exit button
- Menu button
- Mode-switching button
- · Brightness button

Cable Management

Support

Case Color

Black

Dimensions (WxDxH)[1]

Models	Dimensions
Models with full function monitor stand	539.8 x 230.4 x 596.9 mm (21.25 x 9.07 x 23.5 inches)
Models without stand	539.8 x 65.3 x 367.6 mm (21.25 x 2.57 x 14.47 inches)

Packaging Dimensions (WxDxH)

602 x 160 x 422 mm (23.70 x 6.3 x 16.61 inches)

Weight^[2]

Models	Weight
Models with full function monitor stand	Around 6.66 kg (14.68 lbs)
Models without stand	Around 3.61 kg (7.96 lbs)

Packaging Weight

7.6 kg (16.8 lbs)

Mounting

Supports VESA mount 100mm

Stand

Full function monitor stand, supports -5° to +30° tilt, left & right 45° swivel, up to 150mm lift, 90° pivot

In the Box

• 1x Power adapter

ThinkCentre Tiny-In-One 24 Gen 4



- · Detachable stand
- · Power cable
- Quick Setup Guide
- TIO (monitor)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Ports^[1]

Rear Ports

- 1x USB-B 3.1 Gen 1, USB upstream
- 1x DisplayPort™
- 1x power connector

Left Ports[2]

• 1x USB 3.1 Gen 1 (on TIO)

The availability and version depends on the Tiny installed or the PC connected via USB upstream port (USB-B 3.1 Gen 1)

Side ports offered by installed Tiny (on Tiny)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] The availability and version depends on the Tiny installed or the PC connected via USB upstream port.

SECURITY & PRIVACY

Security

Physical Locks

Kensington® Security Slot™, 3 x 7 mm

SERVICE

Warranty

Base Warranty

3-year limited warranty

CERTIFICATIONS

Green Certifications¹¹

Green Certifications

- ENERGY STAR® 8.0
- EPEAT™ Silver Registered^[2]
- ErP Lot 5
- GREENGUARD®
- TCO edge 2.0
- RoHS compliant

ThinkCentre Tiny-In-One 24 Gen 4



• WEEE

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

Other Certifications

Other Certifications

- TÜV Rheinland® Flicker Free
- TÜV Rheinland Eye Comfort Certification
- TÜV Rheinland Low Blue Light
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.























